

4G LTE Home Security Panel Alarm.com



- Multifunctional security panel with 4G LTE Alarm.com
- Supports external antenna
- Incorporates via SF1 868Mhz radio, WiFi, IP, Z-Wave and ZigBee with 4G/LTE capabilities (Alarm.com)
- Bluetooth 5.0 compatible
- Up to 160 devices with remote management capability
- Compatible with IP cameras and PIRCAMS for visual verification and real-time monitoring
- Allows Z-Wave and ZigBee devices to create a home automation system
- Supports MicroSD card



Reference / Model	HSGW-G8-ADC
Security and automation panel compatible with Alarm.com	
Allows up to 160 zones with remote management capabilities via smartphone and web browser	
2 security areas	
Incorporates via radio SF1 868Mhz	
Incorporates Z-Wave 800 module	
Incorporates ZigBee 3.0 module	
Incorporates IP module	
Incorporates WiFi IEEE802.11a/b/g/n/ac	
Bluetooth 5.0 compatible	
Built-in 4G LTE alarm.com module(only compatible with Alarm.com)	
4G LTE frequencies: B1 (2100 MHz), B3 (1800 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz)	
Supports external antenna	
Built-in loudspeaker (for voice indication only)	
95dB siren at 1 meter	
LED indicators	

4G LTE Home Security Panel Alarm.com

Reference / Model	HSGW-G8-ADC
Full programming from Alarm.com's WEB platform/ installer APP	
Compatibility with the large catalog of more than 50 F1 devices: keypads, sirens, smoke sensors, PIR detectors, PIRCAMS, temperature sensors, door contacts, perimeter detectors, vibration sensors, etc. (Note: check compatibility list with Alarm.com)	
Supports indoor and outdoor IP cameras and PIRCAMS (user can make photo requests from the APP)	
Automatic rules programming (e.g. automatic watering, presence simulation, control of any device by calendars, Auto-Arms)	
Remote firmware upgrade	
eMMC storage up to 4GB	
MicroSD card slot (not included)	
External power supply: 100V ~ 240V AC, 50/60Hz (12V DC, 1.5A adapter included)	
Built-in AAA NiMH 600mAh rechargeable 7.2V battery pack with up to 14 hours of battery life	
Operating temperature -10°C ~ +45°C (-10°C ~ +45°C)	
Operating relative humidity up to 85% (non-condensing)	
Dimensions: 185 (W) x 185 (H) x 50 mm	
Weight: 580 g (including battery pack)	